

The Flo-More FMRC-1D2S Series



Applications: Sift/Scalp, Scalp/Scalp, Sift/Sift Grains, Seeds, Pellets and other Bulk Commodities

Capacity: Models available from 500 to 5,000 bushels per hour

Technical Specifications FMRC-1D2S-5000:

Extreme Height	68"	Motor	5HP, 3 Phase, 230/460/60HZ
Extreme Width	55"		Available in 1 Phase and 50HZ
Extreme Length	160"	Drive	Gear Reducer
Weight	3,700 pounds	Options	Aspiration available upon request, Multiple Hoppers or Common Discharge

Features:

- Single Drum, Two Screen
- Total Screen Area –75.40 Ft²
- Sift/Scalp, Sift/Sift or Scalp/Scalp Screen arrangements
- Mild Steel Materials of Construction
- 3/16 Plate Clean Grain Discharge Hoppers
- 3/16 Plate Inlet
- Cleaner Door Panel is 12 Gauge M.S.
- Conveyance Auger Shaft is 6" Schedule 80
- Auger Flights of 7 Gauge M.S. - 36" Diameter
- Screens are 36 inch ID x 48 inches long
- Heavy-duty Bearings and Supports
- One - 5 HP Motor – 3/60/230-460
- One - Gear Reducer Drive
- Adjustable Brush type screen cleaning
- Sheaves, Belts and OSHA-Type Drive Guards
- Completely Assembled & Tested in Shop
- Painted Ross Gray unless otherwise specified

Flo-More Products are designed and manufactured by:

Ferrell-Ross Roll Manufacturing Inc.

3690 FM2856, Hereford, Texas 79045 (U.S.A.)

T: 806-364-9051

F: 806-364-8853

E: sales@ferrellross.com

W: www.ferrellross.com