

The Flo-More FMRS-HD Series



Applications: Scalping or Sifting Grains, Seeds, Pellets and other Bulk Commodities

Capacity: Scalping: Models available from 500 to 3,000 bushels per hour
Sifting: Varies with commodity, 250 to 2,000 bushels per hour

Technical Specifications FMRS-2000HD:

| | | | |
|-----------------|--------------|----------|-----------------------------------|
| Extreme Height: | 67" | Motor: | 3HP, 3 Phase, 230/460/60HZ |
| Extreme Width: | 45" | | Available in 1 Phase and 50HZ |
| Extreme Length: | 91" | Drive: | Gear Reducer |
| Weight: | 1,850 pounds | Options: | Aspiration available upon request |

Features:

- Single Drum Screen
- Total Screen Area –29 Ft²
- Screen scalps off overs or sifts out unders
- Mild Steel Materials of Construction
- 3/16 Plate Clean Grain Discharge Hopper
- 3/16 Plate Inlet
- Cleaner Door Panel is 12 Gauge M.S.
- Conveyance Auger Shaft is 3" Schedule 80
- Auger Flights of 7 Gauge M.S. - 28" Diameter
- Screen is 28 inch ID x 48 inches long
- Heavy-duty Bearings and Supports
- One - 3 HP Motor – 3/60/230-460
- One - Gear Reducer Drive
- Adjustable Brush type screen cleaning
- Sheaves, Belts and OSHA-Type Drive Guards
- Completely Assembled & Tested in Shop
- Painted Ross Gray unless otherwise specified

Flo-More Products are designed and manufactured by:

Ferrell-Ross Roll Manufacturing Inc.

102 FM 2856, (Holly Sugar Road), Hereford, Texas 79045 U.S.A.

T: 806-364-9051

F: 806-364-8853

E: sales@ferrellross.com

W: www.ferrellross.com